

**Amendments to the Claims**

1. *(Original)* A method of controlling writing of a signal to an optical disc and including the step of generating a feedback signal to dynamically tune the source of the said signal, and further comprising the steps of generating a plurality of timing signals serving to define the plurality of sampling windows for selecting data samples from RF signals derived from the signal reflected from the disc, generating a plurality of runlength selection signals to allow for measurement of light reflection at required runlength lands or pits, and measuring light reflected at a run length land or pit in processing means and employing the measured signal as the said feedback signal for the said tuning of the signal source.

2. *(Original)* A method as claimed in Claim 1, wherein the width and/or positions of the sampling windows are programmable.

3. *(Currently Amended)* A method as claimed in ~~Claim 1 or 2~~claim 1, wherein the said RF signals are selected when the runlength signal is high.

4. *(Currently Amended)* A method as claimed in ~~Claim 1, 2 or 3~~claim 1, wherein the runlength selection window comprises the current plus next runlength land or pit.

5. *(Currently Amended)* A method as claimed in ~~Claim 1, 2 or 3~~claim 1, wherein the runlength selection window comprises the previous plus current runlength land or pit.

6. *(Currently Amended)* A method as claimed in ~~anyone or more of the preceding claims~~claim 1, wherein the sampling rate of the said RF signals is at least equal to the frequency of a system channel clock.

7. *(Currently Amended)* A method as claimed in ~~anyone or more of Claims 1-6~~claim 1, wherein the RF sample signals are selected by means of the timing signals within a sample engine.

8. *(Currently Amended)* A method as claimed in ~~anyone or more of Claims 1-7~~claim 1, and including the step of low pass filtering the sampled signals.

9. *(Original)* A method as claimed in Claim 8, and including the step of calculating slope and offset values on the basis of the low pass sampled signals.

10. *(Currently Amended)* A method as claimed in ~~anyone or more of the preceding claims~~claim 1, wherein the feedback signal is arranged for fine-tuning the Write Strategy associated with a DVD writable device.

11. *(Currently Amended)* A method as claimed in ~~anyone or more of the proceedings claims~~claim 1 and including the step of adopting a threshold value serving to determine which of the sampled signals initiate the said measurement.

12. *(Original)* A method as claimed in Claim 11, wherein the selected threshold can be tuned.

13. *(Currently Amended)* A method as claimed in ~~anyone or more of the Claims 1-12~~claim 1, wherein the feedback signal is arranged to fine-tune laser output power of a optical disc writing device.

14. *(Original)* A write signal control apparatus arranged for controlling writing of data to an optical disc and comprising means for generating a feedback signal for dynamically tuning the source of the said signal, means for generating a plurality of timing signals serving to define a plurality of sampling windows, means for selecting data samples for RF signals derived from a signal reflected from the disc, means for generating a plurality of runlength selection signals arranged to allow for measurement of the reflection at a runlength land or pit, and, processing means for measuring the reflected signal at the run length land or pit, wherein the said measured signal serves as the said feedback signal for tuning the said signal source.

15. *(Original)* Apparatus as claimed in Claim 14, wherein the width and/or positions of the sampling windows are arranged to be programmable.

16. *(Currently Amended)* Apparatus as claimed in ~~Claim 14 or 15~~claim 14, wherein signals from the RF analogue-to-digital converter are arranged to be selected when the runlength signal is high.

17. *(Currently Amended)* Apparatus as claimed in ~~Claim 14, 15 or 16~~claim 14, wherein the runlength selection window comprises the current plus next runlength land or pit.

18. *(Currently Amended)* Apparatus as claimed in ~~Claim 14, 15 or 16~~claim 14, wherein the runlength selection window comprises the previous plus current runlength land or pit.

19. *(Currently Amended)* Apparatus as claimed in ~~anyone or more of the preceding claims~~claim 1, wherein the sampling rate of the said RF is at least equal the frequency of a system channel clock.

20. *(Currently Amended)* Apparatus as claimed in ~~anyone or more of Claims 14-19~~claim 14, and including a sample engine in which the said RF sample signals are selected by. means of the timing signals.

21. *(Currently Amended)* Apparatus as claimed in ~~anyone or more of Claims 14-20~~claim 14, and including low pass filter means arranged for low-pass filtering the sampled signals.

22. *(Original)* Apparatus as claimed in Claim 21, and including means for calculating slope and offset values on the basis of the low pass sampled signals.

23. *(Currently Amended)* Apparatus as claimed in ~~anyone or more of Claims 14 to 22~~claim 14 and including means for defining a threshold value serving to determine which sampled signals is employed in the said measurement.

24. *(Original)* Apparatus as claimed in Claim 23, wherein the selected threshold can be tuned.

25. *(Original)* A method of controlling writing of a signal to an optical disc substantially as hereinbefore described with reference to, and as illustrated in the accompanying drawings.

26. *(Original)* Write signal control apparatus arranged for controlling writing of a data to an optical disc and substantially as hereinbefore described with reference to, and as illustrated in the accompanying drawings.